



# i62 SIP Door Phone

## Description

The i62 is a SIP door phone product that integrates access control, intercom, and security functions. It features a technologically advanced design and premium intelligent manufacturing processes, equipped with a quick-dial touch button. The i62 has a high security level, meeting IP66 and IK07 protection standards, making it suitable for outdoor environments. It supports various methods of door opening for efficient access management and comes with a 2 mega pixel camera for one-touch audio and video calls. The i62 supports the SIP and ONVIF protocols, allows for integration with security devices, and is compatible with major mainstream platforms. It can be customized for various scenario solutions, making it suitable for high-end apartment buildings, office buildings, communities, and industrial parks.

## Main Features



One call button for quick contact with the management office.



Equipped with a 2 mega pixel HDR high-definition camera, it provides clearer imaging.



IP66 & IK07 high protection rating, wide temperature operation, suitable for harsh outdoor environments.



Equipped with a wide range of interfaces for connecting various security devices.



Supports the standard ONVIF protocol, providing high flexibility and excellent compatibility.



Fanvil Technology Co., LTD

Add: 10F, Block A, Dualshine Global Science Innovation Center, Honglang North 2nd Road, Bao'An District, Shenzhen, China

Phone: 0755-26402199 E-mail: sales@fanvil.com Web: www.fanvil.com

## Specifications

|                         |                                                                               |
|-------------------------|-------------------------------------------------------------------------------|
| Panel Type              | Multi-apartmentC, ommunity, Hotel, Villa                                      |
| Screen/Keyboard         | Quick call button ×1                                                          |
| Body                    | Aluminum                                                                      |
| Colors                  | Gunmetal                                                                      |
| Sensor                  | 1/2.9-inch, CMOS                                                              |
| Camera                  | 2 Mpx,Support infrared                                                        |
| Viewing Angle           | 120°(Horizontal) 60°(Vertical)                                                |
| Output Video            | H.264 (Baseline, Main Profile)                                                |
| Light Sensitivity       | 0.1Lux                                                                        |
| Card Storage            | 10,000                                                                        |
| Power Consumption       | PoE: 1.69~6.84W<br>Adapter: 1.42~5.93W                                        |
| Power Supply            | DC 12V / 1A<br>POE 802.3af Class 3                                            |
| Working Temperature     | -40℃~+70℃                                                                     |
| Storage Temperature     | -40℃~+70℃                                                                     |
| Size of the Panel (LWH) | 177.4x88x36.15mm                                                              |
| IP / IK Level           | IP66 / IK07                                                                   |
| Installation            | Wall-mounted<br>Flush-mounted(Need to purchase accessories separately: EX102) |

## Functional Capabilities

|                       |                                                                                                        |
|-----------------------|--------------------------------------------------------------------------------------------------------|
| Supported Protocols   | SIP 2.0 over UDP/TCP/TLS                                                                               |
| Lock Opening          | IC/ID Card, By DTMF Code, Remote door opening                                                          |
| Interface             | Wiegand Input/Output<br>Short Circuit Input/Output<br>RS485 (Reserve)<br>Line out for induction loop   |
| Supported Wiegand     | 26, 34 bit                                                                                             |
| Supported ONVIF Types | Profile S                                                                                              |
| Supported Standards   | Mifare Classic 1K/4K, Mifare DESFire, Mifare Ultralight, Mifare Plus<br>Cards 13.56 MHz, Cards 125 kHz |
| Talking Mode          | Full duplex (High-definition Audio)                                                                    |
| Additionally          | Built-in relay, Open API, Motion detection, Tamper alarm, TF Card                                      |